



- Slow drying
- 100% pure non-edible
- Natural wood finish
- Wood preservative

- Contains drying agents
- Protective coating
- Furniture finish
- Exterior or interior use



# Linseed Oils

## Raw Linseed Oil

Highest grade linseed oil available. It is the oldest and best-known natural wood preservative. It forms a tough resistant film on wood, metal or fabric surfaces. It is pure non-edible, slow drying and helps wood retain its natural moisture content, which retards cracking, checking and shrinking and aids water repellency.

## Boiled Linseed Oil

Contains drying agents, which shorten the drying time and enhance the film hardness. This makes it the wiser choice when using on furniture, sealing fences or on sporting goods. Add to oil base paints to enhance brushing and leveling.

## Application

Raw: Preserves wood gutters, farm equipment, caulking, garden tools, etc.

Boiled: Finish floors and furniture, preserve benches, birdhouses, flagpole ropes, garden tools, glazing windows, hand tools, sporting equipment. Makes an anti-spalling compound for concrete when mixed 50/50 with mineral spirits.

**KEEP OUT OF REACH OF CHILDREN  
CLOSE CONTAINER AFTER EACH USE  
NEVER STORE IN UNLABELED CONTAINERS**

**CAUTION:** To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water filled, closed metal container.

Prod Code:	Sizes:	Pkd:	UPC:	Ship Wt:
RAW:				
102004	Quart	6/case	0 82069 63014 5	27 lbs.
102001	Gallon	4/case	0 82069 63011 4	34 lbs.
BOILED:				
102104	Quart	6/case	0 82069 63114 2	26 lbs.
102101	Gallon	4/case	0 82069 63111 1	34 lbs.
102106	5 Gal.	Drum	0 82069 63106 7	40 lbs.
102153	53 Gal.	Drum	0 82069 63105 3	447 lbs.