



- Prepares surface for painting
- Eliminates sanding
- Effective on paint, shellac, varnish and lacquers
- Dulls gloss finishes

Sanding Liquid

Description

Sanding Liquid paint bonder and deglosser assists the professional or homeowner in preparing surfaces for repainting. Sanding Liquid removes polish, scuff marks and caked wax from wood floors and paneling. It eliminates hours of dusty sandpapering before refinishing or painting. The product requires no rinsing or neutralizing.

Application

Sanding Liquid will dull glossy finishes to prepare the surface for a better bond of the new finish. It will soften and smooth rough, crazed and scaled surfaces and prevent crawling. Use on woodwork, paneling, doors and windows. A quarter pint of Sanding Liquid may be added to a gallon of paint, varnish or enamel to give the new finish a tight bond and prevent crawling. This applies to the first coat only. Do not add to latex paints.

Directions

Apply Sanding Liquid with a soft cloth to the surface to be cleaned or dulled. Be sure to turn the cloth frequently to avoid grime build up. Change the cloth when necessary. Wipe with light, even strokes. On hard, glossy finishes, rub more vigorously to properly dull the surface.

Important label information

DANGER:! EXTREMELY FLAMMABLE. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. SKIN AND EYE IRRITANT. VAPOR MAY CAUSE FLASH FIRE. Before use, always read all information and warnings on container. Material Safety Data Sheets available upon request.

**KEEP OUT OF REACH OF CHILDREN
CLOSE CONTAINER AFTER EACH USE
NEVER STORE IN UNLABELED CONTAINERS**

Prod Code:	Sizes:	Pkd:	UPC:	Ship Wt:
051004	Quart	6/case	0 82069 29504 7	13 lbs.