

Industrial Division

TECHNICAL BULLETIN

S.I. No. 14 Coating Remover

PRODUCT DESCRIPTION

This product is a semi-paste, non-methylene chloride coating remover. Formulated for fast stripping of shellac, lacquer, varnish and conventional paints. S.I. No. 14 is formulated for brush application and will not darken fine woods.

OUTSTANDING FEATURES

- Contains no methylene chloride.
- Especially good at removing clear finishes and conventional paints.
- Safe to use on all types of wood, metal and masonry surfaces.
- Clings to vertical, curved and angular surfaces.
- Stripped pieces can be rinsed with water.
- Safe for veneers and fine wood.

CHEMICAL CHARACTERISTICS

Base: Mixed solvent blend Appearance: Thickened liquid

Odor: Aromatic VOC: 6.84 lbs./gal. Flash Point: 24°F (T.C.C.)

Viscosity: >60 Seconds/#4 Ford Cup

WPG: 7.22 lbs. pH (1% in H₂O): 6-7

USE INSTRUCTIONS

Brush product on surface to be stripped with a natural bristle paint brush. Use a heavy, even coat with a loaded brush stroking in one direction only. Leave the remover surface undisturbed until the old finish is completely lifted or softened as determined by a scrape test. Allow approximately twenty minutes for coating to be loosened. The exact time for a particular coating can be determined by testing. When the old finish is completely softened remove the sludge with a scraper or coarse rags. Stripped surface should be cleaned with a good cleaner to remove all remover residue.

Savogran offers a customer service lab that will determine optimum dwell time and appropriate cleaning agent upon request.

SAFETY PRECAUTIONS: **DANGER: FLAMMABLE. Keep away from sparks, heat and flames.** If exhaust fans and/or pumps are used, the motors must be explosion proof. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapors. See material safety data sheet for more complete information.