

SAFETY DATA SHEET

SAVOGRAN COMPANY

1. Product and Company Identification

Product Name: THINX RED Product Code: 1210N

Savogran Company

259 Lenox St

PO Box 130

Norwood, MA 02062-0130

Information Phone: 781-762-5400

Emergency Phone: 800-424-9300

Website Address: www.savogran.com

Synonyms: 100006,100011,100014,100055,
521006,RM#1,Mineral Spirits

Product Use: THINNER

2. Hazards Identification

GHS Ratings:

Flammable liquid	3
Organ toxin single exposure	3
Aspiration hazard	1

GHS Hazards

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H336	May cause drowsiness or dizziness

GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P332+P313	If skin irritation occurs: Get medical advice/attention
P370+P378	In case of fire: Use use carbon dioxide or dry chemical
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with local/regional/national/international regulations

Signal Word: Danger



3. Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
PETROLEUM DISTILLATE	8052413	100.00%

4. First Aid Measures

Inhalation: If illness occurs, remove patient to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, start artificial respiration. Call physician immediately.

Eyes: Flood with plenty of water with eye lids held open for at least 15 minutes and get medical attention promptly.

Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion: Immediately give 1 or 2 glasses of water and call physician, hospital emergency room or poison control center for way to induce vomiting. Get medical attention promptly. Never give anything by mouth to an unconscious person. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.

Note to Physicians: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

5. Fire Fighting Measures

Flash Point: 46 C (115 F)

LEL: 1.0%

UEL: 6.0%

Extinguishing Media: Water fog, regular foam, carbon dioxide or dry chemical.

DANGER! COMBUSTIBLE. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke.

Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone.

May form carbon dioxide and carbon monoxide, various hydrocarbons.

Fire Fighting: Wear self-contained breathing apparatus with full face piece operated in pressure-demand or other positive pressure mode. Straight water steam will spread fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

6. Accidental Release Measures

Methods/Materials for Containment and Cleaning Up:

Eliminate all ignition sources. Runoff may create fire or exposure hazard in sewer system. Absorb on fire retardant, liquid-absorbing material. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal. Prevent spills from entering storm sewers or drains and contact with soil.

Small spill: Wipe or scrap up any material. Wash area thoroughly with detergent and water; ventilate adequately with good fresh air movement at floor level.

Large Spill: Wear proper protective equipment. Stop spill at source, dike area of spill to keep from spreading and keep out of ground water and streams. Transfer material to metal containers. Absorb remainder with sand, clay, earth, floor absorbent or other material and shovel into containers. Then wash area thoroughly with water and detergent. Ventilate adequately with good fresh air movement at floor level. Do not restart pilot lights or operate electrical devices or other sources of sparks, flames or heat until all vapors (odors) are gone.

7. Handling and Storage

Do not breathe material. Keep container closed. Use only with adequate ventilation. Avoid contact with eyes, skin

and clothing. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor and liquid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers should be grounded and/or bonded when material is transferred.

Storage: Keep away from heat. Keep away from sources of ignition. Keep container tightly closed in a cool, well-ventilated place. Keep out of reach of children.

8. Exposure Controls/Personal Protection			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
PETROLEUM DISTILLATE 8052413	500 ppm TWA	100 ppm TWA	Not Established

Engineering Controls:

The vapors are heavier than air and due care must be exercised to prevent them from collecting in low, unventilated areas. Vapors may travel along the floor (even under and around closed doors). Adequate ventilation must be provided with good fresh air movement at floor level by normal cross ventilation or preferably good explosion proof exhaust fans. Limit concentration of any solvent in air to exposure guidelines.

Respiratory Protection:

For known vapor concentrations above the occupational exposure guidelines, use a NIOSH approved organic vapor respirator.

Skin Protection:

Use chemical-resistant gloves to avoid prolonged or repeated skin contact.

Eye Protection:

Chemical goggles or safety glasses with side shield.

9. Physical and Chemical Properties

<p>Appearance: Colorless liquid</p> <p>Vapor Pressure: 2mmHg@20C</p> <p>Vapor Density: 4.9 (Air=1)</p> <p>Sp. Gravity: 0.773</p> <p>Freezing point: No data</p> <p>Boiling range: 149°C</p> <p>Evaporation rate: 151 (Ethyl Ether)</p> <p>Explosive Limits: 1% - 6%</p> <p>Autoignition temperature: 232°C</p> <p>Viscosity: No data</p> <p>Lbs VOC/Gallon: 6.44</p>	<p>Odor: Hydrocarbon odor</p> <p>Odor threshold: No data</p> <p>pH: No data</p> <p>Melting point: No data</p> <p>Solubility: Negligible</p> <p>Flash point: 115F</p> <p>Flammability: No data</p> <p>Partition coefficient (n-octanol/water): No data</p> <p>Decomposition temperature: No data</p> <p>Grams VOC/Literr: 771</p> <p>% Weight Volatile (VOC): 100</p>
---	---

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

STABLE

Incompatibility:

Strong oxidizing agents (e.g. nitric acid, permangantates, etc.), strong alkalies (e.g. NaOH, ammonia, etc.), strong acids (e.g. HCl, sulfuric, etc.)

Hazardous Decomposition:

May form carbon dioxide and carbon monoxide, various hydrocarbons.

Hazardous polymerization will not occur.

11. Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 5,000mg/kg

Dermal Toxicity LD50: 3,000mg/kg

Routes of Entry Anticipated:

Inhalation Skin Contact Eye Contact Ingestion

Potential Health Effects:

Eye: May cause mild eye irritation. Symptoms include stinging, tearing and redness.

Skin: Short contact - no irritation. Prolonged or frequently repeated contact may cause slight irritation.

Ingestion: Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Ingestion can cause blindness, nausea, vomiting, diarrhea, gastrointestinal irritation and death.

Inhalation: Breathing of vapor is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Effects of Overexposure

Contains no ingredients listed as a carcinogen

Aggravation of Pre-Existing Conditions: Persons thought to have heart or respiratory problems should seek medical advice before using solvents of any kind. If signs of allergy develop (breathing difficulty, eye itching, prolonged itching or redness of the skin, headaches, dizziness, etc.) discontinue use of product immediately and consult a physician. Caution: Drinking alcohol shortly before, or after exposure to some solvents may cause undesirable effects.

Chronic: Intentional misuse by deliberately concentrating and inhaling the product may be harmful or fatal. Reports have associated repeated and prolonged overexposure to solvents with permanent brain, nervous system, liver and kidney damage.

12. Ecological Information

Ecotoxicity: Not available.

Persistence and degradability: No data is available on the degradability of this product.

Bioaccumulative potential: Has the potential to bioaccumulate.

Mobility in soil: Adsorbs to soil and has low mobility

Other Adverse effects: No known significant effects or critical hazards.

13. Disposal Considerations

Must be disposed of in accordance with local, state and federal regulations.

14. Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	NOT REGULATED			

15. Regulatory Information

TSCA: The intentional ingredients of this product are listed.

OSHA: The intentional regulated ingredients of this product are listed.

CERCLA: SARA Hazard Category: Immediate/Fire

SECTION 313: Not Listed

None of the chemical(s) in this material have an RQ.

New Jersey RTK label Information

8052413 PETROLEUM DISTILLATE

Pennsylvania RTK Label Information

16. OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	<input type="text" value="1"/>
FLAMMABILITY	<input type="text" value="2"/>
PHYSICAL HAZARD	<input type="text" value="0"/>
PERSONAL PROTECTION	<input type="text"/>

HMIS & NFPA Hazard Rating

Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



Judgement of potential hazards of this product is based on informatoin available about individual components listed under section 3 - Ingredients. Direct testing of mixture has not been done. Information given herin is believed to be accurate and is given in good faith. However, no warranty either expressed or implied is made. It is strongly suggested tht users confirm in advance of need that the information is current and applicable to their situations.

Date revised: 2019-07-16

Reviewer Revision 1

Date Prepared: 7/16/2019