# SAFETY DATA SHEET

## SAVOGRAN COMPANY

#### 1. Product and Company Identification

Product Name: TILE GROUT PRE-MIXED Product Code: 860N

Savogran Company 259 Lenox St PO Box 130

Norwood, MA 02062-0130 Information Phone: 781-762-5400 Emergency Phone: 800-424-9300 Website Address: www.savogran.com

Synonyms: 12860,12861,12862

Product Use: TILE GROUT

### 2. Hazards Identification

This product does not meet the hazardous criteria set forth by the 2012 OSHA Hazardous Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

### **GHS Ratings:**

There are no GHS ratings that apply to this product at this time

### **GHS Hazards**

There are no GHS hazards that apply to this product at this time

### **GHS Precautions**

There are no GHS precautons that apply to this product at this time

## 3. Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
LIMESTONE	1317-65-3	70.00% - 80.00%
ACRYLIC POLYMER	MIXTURE	20.00% - 30.00%
PROPYLENE GLYCOL	57-55-6	1.00% - 5.00%
QUARTZ	14808-60-7	1.00%

#### 4. First Aid Measures

Inhalation: If illness occurs, remove patient to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, start artificial respiration. Call physician immediately.

Eyes: Flood with plenty of water with eye lids held open for at least 15 minutes and get medical attention promptly. Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion: If accidently swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

SDS for: 860N Page 1 of 4

## 5. Fire Fighting Measures

Flash Point: N/A

LEL: N/A UEL: N/A

No flammable properties.

Extinguishing Media:Not combustible. Use extinguishing method suitable for surrounding fire.

Hazardous Combustion Products: May form carbon dioxide and carbon monoxide.

Firefighting Procedures: Wear appropriate personal protective equipment.

## 6. Accidental Release Measures

No special precautions.

### 7. Handling and Storage

Store and handle in accordance with all current regulations and standards. Wash thoroughly with soap and water after handling. While handling product keep out of reach of children. Do not eat or drink while handling this material.. Keep container tightly closed.

## 8. Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
LIMESTONE 1317-65-3	15 mg/m3 TWA, (total dust) 5 mg/m3 TWA (respirable fraction)	Not Established	Not Established
ACRYLIC POLYMER MIXTURE	Not Established	Not Established	Not Established
PROPYLENE GLYCOL 57-55-6	Not Established	Not Established	Not Established
QUARTZ 14808-60-7	30 mg/m3 %SiO2+2 TWA (total dust)/ 10 mg/m3 %SiO2+2 TWA (respirable) 250 mppcf %%SiO2+5 TWA (respirable)	Not Established	Not Established

No PPE required when used as intended.

# 9. Physical and Chemical Properties

Appearance: No data

Vapor Pressure: No data

Vapor Density: No data

Density: 15.6

Freezing point: No data

Odor: Mild ammoniacal

Odor threshold: No data

pH: 8.5-9.0 (1% H2O)

Melting point: No data

Solubility: Dispersable

SDS for: 860N Page 2 of 4

Boiling range: No data Evaporation rate: No data

**Explosive Limits: N/A** 

Autoignition temperature: No data

Viscosity: No data

Flash point: N/A

Flammability: No data

Partition coefficient (n- No data octanol/water):

Decomposition temperature: No data

Grams VOC less water: 0

### 10. Stability and Reactivity

Chemical Stability (Conditions to Avoid): Stable

**STABLE** 

Incompatibility:

None known

Hazardous Decomposition Products:

No hazardous combustion products are known.

Hazardous polymerization will not occur.

## 11. Toxicological Information

### **Mixture Toxicity**

Not tested as a whole.

Routes of Entry Antiicipated:

Inhalation Ingestion

#### **Effects of Overexposure**

Silica, Crystalline as Quartz (CAS#14808-60-7) is present in Calcium Carbonate filler. If sanded, this material may generate silica dust. Inhaled silica has been classified by IARC as a human carcinogen.

## 12. Ecological Information

This product has no known adverse effect on ecology.

# 13. Disposal Considerations

Small quantities may be deposited in general trash and residue flushed down drain with water. Large spills must be disposed of in accordance with local, state and federal regulations.

### 14. Transport Information

**Proper Shipping Name** <u>Agency</u> DOT **NOT REGULATED** 

**UN Number** Packing Group Hazard Class

## 15. Regulatory Information

TSCA: The intentional ingredients of this product are listed.

OSHA: The intentional regulated ingredients of this product are listed.

New Jersery RTK label Information

57-55-6 PROPYLENE GLYCOL

Pennsylvania RTK Label Information 57-55-6 PROPYLENE GLYCOL

SDS for: 860N Page 3 of 4

### 16. OTHER INFORMATION

# **Hazardous Material Information System (HMIS)**



HMIS & NFPA Hazard Rating Legend

\* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

## **National Fire Protection Association (NFPA)**



Date revised: 2019-08-20 Reviewer Revision 1

Date Prepared: 8/20/2019

SDS for: 860N Page 4 of 4

Printed: 8/20/2019 at 8:28:59AM